

SPECIALTY BALL VALVES

T/S-2000 FORGED BRASS

ISO 9002



Full Port
Gland Follower Design

MSS SP-110
600 CWP
150 WSP

Blow-out proof stem
PTFE seats

Sizes: Threaded 1/4" to 4"
Solder 1/2" to 4"

CSA Certified
UL Listed
Meets ANSI / NSF 61-8

T-1002LD FORGED BRASS

ISO 9002



Full Port
Gland Follower Design

MSS SP-110
600 CWP
150 WSP

Blow-out proof stem
PTFE seats

Locking device

Sizes: Threaded 1/4" to 2"

CSA Certified,
UL Listed
FM Approved

**Also Available: T-1002STLD
316 Stainless steel ball & stem
and Locking device**

T/S-1002FLG BRASS

ISO 9002



Full Port Flanged Isolation Valve
Gland Follower Design

MSS SP-110
600 CWP
150 WSP

Blow-out proof stem
PTFE seats

Bolt set included

Sizes: Threaded 3/4" to 1-1/4"
Solder 3/4" to 1-1/4"

**Also Available: T/S-2012RFLG BRASS
Drainable with
Rotating Flange**


T-1001LD FORGED BRASS

ISO 9002



Full Port
O-Ring Design

MSS SP-110
600 CWP
150 WSP

Blow-out proof stem
*Dyneon™ TFM PTFE seats

Locking device

Sizes: Threaded 1/2" to 2"

CSA Certified to
ANSI/NSF 61
UL Listed
FM Approved

T-1002CC SPECIALITY - FORGED BRASS

ISO 9002



Full Port
Gland Follower Design

MSS SP-110
600 CWP (Body)
200 CWP rated end connections

Blow-out proof stem
PTFE seats

Cap & chain

Sizes: Threaded
3/4" FIP x 3/4" GHT