

# Penal-Ware<sup>®</sup> 1741 Series

Penal-Pak - Wall Shower

Ø		
00		
1741-04-M-RD		
Fixture May Show Some Available Options		
Please visit <b>www.acorneng.com</b> for most current specifications.		

# Penal-Pak - Wall Shower

**Shower** is arranged to be installed on finished wall and serviced from an accessible pipe chase. Back of shower is provided with anchor tappings. Optional Wall Sleeve or Metal Template is recommended for all installations for required wall openings. Fixture is fabricated from 14 gage, type 304 stainless steel with a satin finish.

**Showerhead** is chrome plated brass and is vandal-resistant. The nozzle is threaded into the body and then locked into place by a set screw from the rear. The spray pattern can only be changed by use of an allen wrench inserted through the nozzle.

**Valve** is a pneumatically operated, pushbutton Air-Control valve using atmospheric air. Pushbutton is vandal-resistant and requires less than 5 pounds to activate valve. Valve is metering, non-hold open type. Valve timing is adjustable from 5 to 60 seconds. Valve includes a 2.5 GPM flow control (not available in California, see Product Options for alternate choices) and can be remotely located up to 10 feet from the operating pushbutton. Valve conforms with lead free requirements of NSF61, Section 9.

**Regularly furnished** items include an metering Air-Control valve, a showerhead and mounting hardware for walls up to 8" thick.

# **GUIDE SPECIFICATION**

Provide and install Acorn Penal-Pak - Wall Shower (specify model number and options). Shower panel shall be fabricated from 14 gage, type 304 stainless steel and shall have a satin finish. Trim shall be stainless steel or chrome-plated brass. Shower valve shall be Air-Control, metering, non-hold open type. Fixture shall be furnished with necessary fasteners for proper installation.

Page 1 P.1741

Revised: 03/01/17

#### Get Started Www.mgispecbuilder.com

# Penal-Ware®: 1741 Penal-Pak - Wall Shower

WALL THICKNESS AND TYPE (Must Specify)

Type: Concrete Block Steel Thickness:

## MODEL NUMBER AND OPTIONS SELECTION:

## **BASE MODEL NUMBER**

1741 Penal-Pak Wall Shower

### VALVE SELECTION (Must Specify)

**Air-Control (Pneumatic)** 

🗋 -03-M Single Temp, Metering 🗋 -04-M Hot & Cold, Metering

#### Master-Trol<sup>®</sup> (Electronic)

🗋 -EVS1	Single Temp
🗋 -EVS2	Hot & Cold
-EVSP1	Single Temp, Piezo Button
-EVSP2	Hot & Cold, Piezo Buttons

### Master-Trol<sup>®</sup> PLUS (Electronic)

🗋 -MTP1 Single Temp 🗋 -MTP2 Hot & Cold -MTPP1 Single Temp, Piezo Button -MTPP2 Hot & Cold, Piezo Buttons

#### Time-Trol<sup>®</sup> (Electronic)

	(=======
-MVC1	Single Temp
🗋 -MVC2	Hot & Cold

# Programmable (Electronic) w/9VDC Plug-In Transformer

Single Temp Programmable Piezo Button 🛄 -PPZ1

🗆 -PPZ2 Hot & Cold Programmable Piezo Button

# Valve By Others

Punched for Valve by Others **-**9

### VALVE OPTIONS

- Brass Body Valve -BRS
- -MA2 Manifolded, 2-Stack
- 🔲 -PBH Hemispherical Pushbutton
- Transformer, 120VAC to 24VAC (-MVC option only) 🗋 -TF

## SHOWERHEAD OPTIONS


- 🗋 -CSH Conical Showerhead
- Flow Control 🗋 - F
  - 1.4 GPM 1.6 GPM
  - 2.0 GPM (Not available in California)
- -PYY Penal Showerhead w/Lockable Universal Ball Joint
- 🗋 -PZZ Penal Showerhead w/Lockable Up-Down Ball Joint
- -SSV Space Saver Showerhead 20 Degree Discharge

## **PRODUCT OPTIONS**

- 🗋 D Soap Dish
- 🗋 -EG Enviro-Glaze, Specify Color:\_
- -MT Metal Template (Only 1 Required Per Project)
- -RD Recessed Soap Dish
- 🗅 -SW Wall Sleeve


Please visit *www.acorneng.com* for most current specifications.

MODEL	"A"
Single Temp Valve	8" (203)
Hot and Cold Valve	10" (254)



NOTES:

- 1. Optional -03 Air-Control Valve
- 2. Penal Shower Head
- 3. Optional -D Surface Mounted Soap Dish



4. Penal Pushbutton

5. Wall Mounting Hardware

Important: Installation instructions and current rough-in are furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of plus or minus 1/4" and change without notice. Acorn assumes no responsibility for use of void or superseded data. © Copyright 2009 Acorn Engineering Company				
Selection Summary	Approved for Manufacturing			
Model No. & Option	CompanyTitle			
Quantity	Signature Date			
Page 2 P.	<b>1741</b> <i>Revised: 03/01/17</i>			

1741-03-D

Acorn Engineering Company • 15125 Proctor Avenue • P.O. Box 3527 • City of Industry, CA 91744-0527 U.S.A. Tel: (800) 488-8999 • (626) 336-4561 • Fax: (626) 961-2200 • www.acorneng.com • E-mail: info@acorneng.com