





THERM-X-TROL®

Water Heater Expansion Tanks

Specifications



ST-5, ST-8, ST-12



ST-25V through ST-210V

Model Number	Tank Volume (Gallons)	Max. Accept. Volume (Gallons)	A Diameter (Inches)	B Height (Inches)	System Connection	Shipping Weight (lbs.)
ST-5	2.0	0.9	8	13	¾ NPTM	5
ST-8	3.2	1.9	9	15	¾ NPTM	7
ST-12	4.4	3.2	11	15	¾ NPTM	9
ST-25V	10.3	10.3	15	19	¾ NPTF	23
ST-30V	14.0	11.3	15	24	¾ NPTF	25
ST-42V	20.0	11.4	15	32	¾ NPTF	33
ST-60V	34.0	34.0	22	30	1¼ NPTF	61
ST-80V	44.0	33.9	22	36	1¼ NPTF	69
ST-180V	62.0	34.1	22	47	1¼ NPTF	92
ST-200V	81.0	33.2	22	56	1¼ NPTF	103
ST-210V	86.0	46.4	26	47	1¼ NPTF	123

Stainless Steel System Connection.

Maximum Operating Temperature: 200°F.

Maximum Working Pressure 150 psig. Factory Pre-charge: 40 PSIG.

THERM-X-TROL® Quick Sizing Charts

Maximum Temperature Setting 140°F				Maximum Temperature Setting 160°F				Maximum Temperature Setting 180°F			
Water Heater Size (gals.)	Static Supply Pressure (psig)			Water Heater Size (gals.)	Static Supply Pressure (psig)			Water Heater Size (gals.)	Static Supply Pressure (psig)		
	40	60	80		40	60	80		40	60	80
40	ST-5	ST-5	ST-5	40	ST-5	ST-5	ST-8	40	ST-8	ST-8	ST-8
50	ST-5	ST-5	ST-5	50	ST-5	ST-8	ST-8	50	ST-8	ST-8	ST-12
60	ST-8	ST-8	ST-8	60	ST-8	ST-8	ST-12	60	ST-8	ST-12	ST-25V
80	ST-8	ST-8	ST-12	80	ST-8	ST-12	ST-25V	80	ST-12	ST-25V	ST-25V
120	ST-12	ST-12	ST-25V	120	ST-12	ST-25V	ST-25V	120	ST-25V	ST-25V	ST-25V

Sizing based on: 40°F incoming water temperature; 150 psi T&P safety relief valve; Pre-charge equal to static supply pressure. For larger applications: Visit amtrol.com, download the AMTROL App or contact Technical Support at 401.535.1216.



NSF/ANSI 61



PLUMBERS-HEATING-AND-COOLING CONTRACTORS ASSOCIATION

