



PRODUCT SHEET

AMMA OVAL 6638

66 x 38 x 21

Redefined massage. Ideal comfort.



© BAINULTRA®

FEATURES	
Installation type	Drop-in
No. of bathers	1
Raised seat	1
Heated backrest	1
Heated headrest	1
Inverted V	1
Armrests	2
Grab bars (color match)	2
Control	MiaPlus
ThermoMasseur® bath	\$
Soaker bath	N/A

THERAPIES	
Chromatherapy 2-LED	\$
Sound Therapy (Euphonia™ System)	\$

COLORS	
Standards	
White	Bone Biscuit Almond
Optionals	
Black	Mexican sand Innocent blush Cashmere Sandbar Grey

WARRANTY	
Controls*	5 years
Bath & turbine*	20 years
*Some restrictions apply www.bainultra.com/warranty	



IMPORTANT: KEEP THE ORIGINAL. PLEASE MAKE COPIES.

AMMA®: AMMA 6030, AMMA 6032, AMMA 6036, AMMA 6636, **AMMA OVAL 6638**, AMMA 6060, AMMA 7048, AMMA 7236, AMMA 7242, AMMA OVAL 7242, AMMA OVAL 7242 FREESTANDING

BainUltra®

The quest for your wellness™
www.bainultra.com




AMMA OVAL 6638 66 x 38 x 21

ACCESSORIES - OPTIONAL

Clear acrylic grab bars	With Chrome, Brass or Brushed nickel inserts	\$
Drain & overflow	D-10 (17" - 22")	
	- Chrome	\$
	- White, Biscuit, Bone	\$
	- Brass	\$
	- Brushed nickel, Polished nickel, Oil-rubbed bronze	\$

Control	MiaMulti	\$
Cutting template	# 90000037	

TOTAL PRICE	\$
--------------------	----



LETTER	DESCRIPTION	MEASURE
A	Outside edge to center drain	9 3/4"
B	Outside edge to overflow	3 3/4"
C	Total length	66"
D	Total width	38"
E	Bathing well length	52 1/4"
F	Bathing well width at foot area	18"
G	Raised seat length	21"
H	Raised seat width	20 7/8"
I	Flat surface width	3 7/8"
J	Deck width	4 7/8"
K	Deck width at drain end	3 1/4"
L	Total height to headrest	23 1/8"
M	Height from bottom of tub to top deck	21"
N	Height from bottom of tub to bottom of lip	19 1/2"
O	Height from drain to center of overflow	17"
P	Maximum water level	15 3/8"
Q	Slope of backrest	18"

- T** Indicates turbine position
- L** Indicates LED light position
- Indicates heated backrest
- C** Indicates control position when factory-installed

AMMA OVAL 6638 TECHNICAL SPECIFICATIONS

Jets	49
US gallons	56
Imp. gallons	47
Approx. shipping weight	147 lbs
Turbine power	755 W
Air heater	700 W

Hot water supply required	Should be 70% of water capacity of tub or greater.
Turbine access	Must be at least 18" X 22" to access the pump. Must be connected to a 15 A, 120 V, 60 Hz, protected by a ground-fault circuit interrupter (GFCI) on a dedicated line.
Standards	All BainUltra products meet and/or exceed the highest quality and certification standards. For further details about BainUltra's product standards, please go to the following link: (www.bainultra.com/standards).
Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation).	

1 800 463.2187 | From 8 a.m. to 8 p.m. Monday to Thursday (EST) . From 8 a.m. to 5 p.m. on Friday (EST)

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.