

FREESTANDING THEATRE STAGE®

THERMOMASSEUR® BATH	\$	\$
THERMASENS™ BATH	\$	\$
SOAKER BATH	N/A	N/A

THERMOMASSEUR (TMU)	
Jets	58
2 heated backrests (Independently controlled)	included
2 heated headrests (Independently controlled)	included
MiaPlus® Control	included
Geysair™	\$
AromaCloud™	\$
Chromatherapy - LED	\$

THERMASENS (TMSU)	
AromaCloud™	included
Chromatherapy - LED	included
WarmTouchShell™	included
2 DOT controls	included
2 nd WarmTouchShell	\$

FEATURES INCLUDED			
Installation type	Freestanding & Theatre Stage		
No. of bathers	22	Inverted V	2
US gallons	65	Armrests	4
Imp. gallons	54	Grab bars (color match)	2
Raised seats	2	Drain & overflow	inst. & incl.

 Choo Choo 	RS e the bath colors se the bath color from standard or optional colo se the base color same as bath color or wood. se the exterior shell color from standard, or opti	
Option	al colors - bath + exterior shell	\$
Option	al colors for interior shell only	\$
Option	al colors for exterior shell only	\$
White	Bone Biscuit Almond	
Option Black	Mexican Cashmere Sandbar Gray	\$
CONT	ROL (TMU ONLY)	
MiaMulti® \$		\$
CLEA	R ACRYLIC GRAB BARS	





AMMA OVAL 7242 (FREESTANDING) 72" X 42" X 28"

ACCESSORIES (OPTIONAL)

9000036 (drop-in, freestanding) **CUTTING TEMPLATE** # 90000059 (theatre stage)


OTHERS


- There is a height difference for the flat deck (see drawing Detail A).
- Turbine located under bath and accessible by a removable base cover.
- Faucets might be installed on deck of bath. Overflow preinstalled for easier in-home fitting.
- Specify flat or raised deck.


TOTAL PRICE

\$

FREESTANDING INSTALLATION









LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	13 1/2"
В	Outside edge to overflow	5 3/8"
С	Total length	72"
D	Total width	42"
E	Bathing well length	52 1/4"
F	Bathing well width at foot area	21 3/8"
G	Raised seat length	18 5/8"
Н	Raised seat width	24"
I	Flat surface width	3 7/8"
J	Deck width	5 1/4''
K	Total height to headrest	29 7/8"
L	Height from bottom of tub to top deck	27 5/8"
M	Height from bottom of lip to top deck	2"
N	Height from drain to center of overflow	18 1/8"
0	Maximum water level	16 3/8"
P	Slope of backrest	18°

- Indicates turbine position (TMU)
- Indicates heated backrest (TMU)
- Indicates LED light position
- Indicates control position when factory-installed

Available with raised or flat deck.

THEATRE STAGE® INSTALLATION





Q	Height from bottom of tub to top deck	29 7/8"
R	Base length	56 1/2"
S	Stage height	10"
Т	Base width	361/2"

TECHNICAL SPECIFICATIONS

Hot water supply required	Should be 70% of water capacity of tub or greater.
Turbine	Access to the pump must be at least 18" X 22". Standard connection is a 20 A. 120 V, 60hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). With the Geysair, a second dedicated line, GFCI protected, 15A. 120 V, 60 hz is needed for the WarmTouch-Shell and additional options. Air vent is necessary: 2" X 4" minimum.

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentations).

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.

Approx. shipping weight	290 lbs
Turbine power	755 W
Air heater	1 000 W

WARRANTY	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

*Some restrictions apply | www.bainultra.com/warranty



