




PRODUCT SHEET
ELLIPSE 6636
 66" X 36" X 21"













THERMOMASSEUR® BATH	\$
THERMASENS™ BATH	\$
SOAKER BATH	\$


THERMOMASSEUR (TMU)	
Jets	38
1 heated backrest	included
MiaPlus® Control	included
Geysair™	\$
AromaCloud™	\$
Chromatherapy - LED	\$

THERMASENS (TMSU)	
AromaCloud™	included
Chromatherapy - LED	included
WarmTouchShell™	included
2 DOT controls	included

FEATURES INCLUDED			
Installation type	Drop-in & Undermount*		
No. of bathers		Imp. gallons	40
US gallons	48		

OPTIONAL UPCHARGE APPLICABLE	
COLORS	
Standards	
	White
	Bone
	Biscuit
	Almond
Optionals	
	Black
	Mexican sand
	Cashmere
	Sandbar
	Gray
	\$
CONTROL (TMU ONLY)	
MiaMulti®	\$
DRAIN & OVERFLOW	
	16" X 35"
Chrome	\$
White, Biscuit & Bone	\$
Brass	\$
Brushed nickel, Polished nickel & Oil-rubbed bronze	\$

 DON'T FORGET TO INDICATE FLAT OR ROLLED DECK.
 * THE AROMACLOUD IS NOT AVAILABLE WITH UNDERMOUNT INSTALLATION.

1 800 463.2187  info@bainultra.com | From 8 a.m. to 8 p.m. Monday to Thursday (EST)
 From 8 a.m. to 5 p.m. on Friday (EST)

ELLIPSE 6636 66" X 36" X 21"

ACCESSORIES (OPTIONAL)

CUTTING TEMPLATE


90000055

OTHERS


- There is a height difference for the rolled deck (see drawing Detail A).

TOTAL PRICE



\$



A
For rolled deck:
Deck modified
to host the
AromaCloud



A
With flat deck,
the AromaCloud
is built into
the deck
(DOT control,
standard location)



Available with flat or rolled deck.

LETTER	DESCRIPTION	MEASURE
A	Outside edge to center drain	11 1/2"
B	Outside edge to overflow	4 5/8"
C	Total length	66"
D	Total width	36"
E	Bathing well length	42 3/8"
F	Bathing well width	22 1/4"
G	Deck width at backrest end	4 3/8"
H	Flat surface width	4 1/4"
I	Rollled deck width	4 3/4"
J	Height from bottom of tub to top deck	21"
K	Height from bottom of tub to top deck	22"
L	Height from bottom of tub to bottom of lip	19 1/2"
M	Height from bottom of lip to top deck	2 1/2"
N	Height from drain to center of overflow	16 5/8"
O	Maximum water level	14 7/8"
P	Slope of backrest	25°

T Indicates turbine position (TMU)

L Indicates LED light position

● Indicates heated backrest (TMU)

L Indicates LED light position

C Indicates control position when factory-installed

☞ Indicates WarmTouchShell position (TMSU)

A Indicates AromaCloud position

TECHNICAL SPECIFICATIONS

Hot water supply required	Should be 70% of water capacity of tub or greater.
Turbine	Access to the pump must be at least 18" X 22". Standard connection is 15 A, 120 V, 60 hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). With Geysair, upgrade to 20 A, 120 V, 60 hz, dedicated line GFCI is needed. For any additional option with the Geysair, a second line is needed 15 A, 120 V, 60 hz, dedicated line with a GFCI. Air vent necessary: 2" X 4" minimum.

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentations).

Approx. shipping weight	100 lbs
Turbine power	755 W
Air heater	700 W

WARRANTY

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

*Some restrictions apply | www.bainultra.com/warranty

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0,64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.

