

THERMOMASSEUR® BATH	\$
THERMASENS™ BATH	\$
SOAKER BATH	\$

THERMOMASSEUR (TMU)	
Jets	42
1 heated backrest	included
MiaPlus® Control	included
Geysair™	\$
AromaCloud™	\$
Chromatherapy - LED	\$

THERMASENS (TMSU)	
AromaCloud™	included
Chromatherapy - LED	included
WarmTouchShell™	included
2 DOT controls (standard location)	included
2 nd WarmTouchShell	\$

FEATURES INCLUDED			
Installation type		Drop-in, Alcove (3 walls) & Ui	ndermount*
No. of bathers	22	Imp. gallons	39
US gallons	47		

OPTIONAL UPCHARGE APPLICABLE								
COLO	RS							
Standa	rds							
White	Bone	Biscuit	Almond					
Option	als						\$	
Black	Mexican sand	Cashmere	Sandbar	Gray				
CONT	ROL (TI	IU ONLY)					
MiaMul	ti®						\$	
SKIRT	S		М	ULTIFIT	ELE	GANCE		SJ-1
Skirts			\$		\$		\$	
Optiona	al colors		\$		\$		\$	
DRAIN & OVERFLOW						16" X 35"		
Chrome				\$				
White, Biscuit & Bone			\$					
Brass			\$					
Brushed nickel, Polished nickel & Oil-rubbed bronze				\$				
TILE FLANGE								
Ordered with bath, uninstalled				\$				
Factory-installed				\$				
VIZ				EL ANCE FOR T				





MERIDIAN 55 66" X 36" X 20"


ACCESSORIES (OPTIONAL)


CUTTING TEMPLATE	# 9000007

Optional tile flange (specify front or back). If ordered with an installed tile flange and a back drain, the control will be shipped separately.
--

TOTAL PRICE

\$





LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	11 3/8"
В	Outside edge to overflow	4 1/4"
С	Total length	65 1/2"
D	Total width	35 3/4"
E	Bathing well length	46 1/8"
F	Bathing well width	23 1/4"
G	Deck width at backrest end	4 3/8"
Н	Deck width	4"
ı	Height from bottom of tub to top deck	20 1/4"
J	Height from bottom of tub to bottom of lip	18 3/4"
K	Height from drain to center of overflow	16 1/8"
L	Maximum water level	14 3/8"
М	Slope of backrest	24°
N	Slope of backrest	15°

Indicates turbine position (TMU)
Indicates heated backrest (TMU)

■ Indicates LED light position

Indicates control position when factory-installed

When tiling flange is added, the AromaCloud will automatically be installed on the opposite side of the flange.

TECHNICAL SPECIFICATIONS

Hot water supply required	Should be 70% of water capacity of tub or greater.
Turbine	Access to the pump must be at least 18" X 22". Standard connection is 15 A. 120 V, 60 hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). With Geysair, upgrade to 20 A. 120 V, 60 hz, dedicated line GFCI is needed. For any additional option with the Geysair, a second line is needed 15 A. 120 V, 60 hz, dedicated line with a GFCI. Air vent necessary: 2" X 4" minimum.

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentations).

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.

Approx. shipping weight	127 lbs
Turbine power	755 W
Air heater	700 W

WARRANTY	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

*Some restrictions apply | www.bainultra.com/warranty



