

FREESTANDING THEATRE STAGE®

THERMOMASSEUR® BATH	\$ \$
THERMASENS™ BATH	\$ \$
SOAKER	\$ \$

THERMOMASSEUR (TMU)		
Jets	37	
1 heated backrest	included	
1 heated headrest	included	
MiaPlus® Control	included	
Geysair™	\$	
AromaCloud™	\$	
Chromatherapy - LED	\$	

THERMASENS (TMSU)	
AromaCloud™	\$
Chromatherapy - LED	\$
WarmTouchShell™	\$
2 DOT controls	included

FEATURES INCLUDED			
Installation types		Freestanding & T	heatre Stage
No. of bather	•	Integrated Headrest	1
US gallons	50	Drain & overflow with face plate	included
Imp. gallons	41		

0	PTIONS
С	OLOR
ĺ	tandard hite
D	PRAIN & OVERFLOW
С	hrome, White
В	rass, Brushed Nickel, Polished Nickel

OPTIONAL UPCHARGE APPLICABLE		
CONTROL (TMU ONLY)		
MiaMulti®	\$	





ORA OVAL 6838 FREESTANDING 68" X 38" X 25"

ACCESSORIES (OPTIONAL)

Cutting Template	# 90000060	
------------------	------------	--

OTHERS


Faucet can be freestanding or installed on the deck (specify overflow side or opposite side). For faucet installed on the deck, the conceiled side of the bath has a full height insert. When


side of the bath has a **full height insert**. When only the Aromacloud is installed on the deck, a **short insert** is built in the concealed side of the bath (See technical drawings below).


TOTAL PRICE

\$


FREESTANDING INSTALLATION








Short Insert for AromaCloud installed on the deck.







LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	18 3/8"
В	Outside edge to overflow	4"
С	Total length	68"
D	Total width	38"
E	Bathing well length	44 1/4''
F	Bathing well width	23 1/8"
G	Distance from center air intake to center drain	4 1/4''
Н	Deck width at backrest end	1 3/8"
I	Total height to headrest	25"
J	Height from drain to top deck	19 1/2"
K	Slope of backrest	25°
L	Base length	52"
М	Base width	28"
N	Deck thickness	7/8"
0	Height from drain to center of overflow	16 5/8"
P	Maximum water level	15 7/8"
Q	Short Insert width	45 1/2"
R	Short Insert height	5"
S	Full Height Insert top width	30"
Т	Full Height Insert bottom width	22 1/8"

(TMU)

Indicates LED light position


■ Indicates heated backrest (TMU)

(≋) Indicates WarmTouchShell position (TMSU)

A Indicates AromaCloud position

Notes: Control will be installed on the opposite side of the AromaCloud. Insert can be located on the overflow side or opposite side.

THEATRE STAGE® INSTALLATION





U	Height from bottom of tub to top deck	25"
٧	Stage height	10"
W	Base length	56 3/4"
х	Base width	31 1/4"

TECHNICAL SPECIFICATIONS

Hot water supply required	Should be 70% of water capacity of tub or greater.
Turbine	Access to the pump must be at least 18" X 22". Standard connection is 15 A. 120 V, 60 hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). With Geysair, upgrade to 20 A. 120 V, 60 hz, dedicated line GFCI is needed. For any additional option with the Geysair, a second line is needed 15 A. 120 V, 60 hz, dedicated line with a GFCI. Air vent necessary: 2" X 4" minimum

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentations).

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.

Approx. shipping weight	250 lbs
Turbine power	600 W
Air heater	700 W

WARRANTY	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

*Some restrictions apply | www.bainultra.com/warranty



