

Commercial Large Volume Unjacketed and Uninsulated Storage Tanks



Photo is of
NV280NG5A

The Large Volume Unjacketed and Uninsulated Storage Tank Models Feature:

- **Vertical or Horizontal Construction**—Horizontal models require two saddles and have two additional 3" NPT fittings.
- **Bare Storage Tank**—Heavy gauge steel primed with a red oxide color.
- **Vitraglas[®] Lining**—Bradford White tanks are lined with an exclusively engineered enamel formula that provides superior tank protection from the highly corrosive effects of hot water. This formula (Vitraglas[®]) is fused to the steel surface by firing at a temperature of over 1600°F (871°C).
- **Water Connections**—Two female 3" NPT fittings are located on the front for ease of service and installation. Additional size fittings are available as an option.
- **Magnesium Anode Rods**—Provide added protection against corrosion for long trouble-free service.
- **One 3/4" NPT Aquastat Fitting**—Located in the lower part of the tank.
- **Lifting Lugs**—Standard.
- **Optional Handhole Cleanout and Manway**—4" x 6" diameter Handhole cleanout and 12"x16" diameter Manway opening allows removal of sediment and inspection of interior surface.
 - Manway required on all tanks with a vessel diameter of 42" or greater.
- **Optional HydroJet HC[®]**—Stainless steel, dielectrically isolated recirculation tube minimizes turbulence and directs the hottest water to the top of the tank to maximize hot water delivery.
- **Designed for Storage of Potable Water up to 180°F (82°C).**
- **All Tanks are Constructed and Certified**—In accordance with ASME Sect. IV, Part HLW for 125 PSI (862 kPa). 150 PSI (1034 kPa) is available as an option.

Sample Specification:

The storage tank shall be a Bradford White Unjacketed and Uninsulated model with an actual rated storage capacity of not less than _____ gallons (_____ liters), and overall dimensions of _____ inches (_____ cm.) in height, by _____ inches (_____ cm.) in diameter. The tank shall be Vitraglas[®] lined, and be built in accordance with ASME Boiler and Pressure Vessel Code ASME IV, Part HLW for 125 PSI (862 kPa) and so labeled, with a working pressure of _____ P.S.I (_____ kPa). The storage tank shall carry a five (5) year limited warranty (ten (10) year limited warranty available on Double Vitraglas[®] lining).



5-Year Limited Tank Warranties / 1-Year Limited Warranty on Component Parts.

For more information on warranty, please visit www.bradfordwhite.com

For products installed in USA, Canada and Puerto Rico. Some states do not allow limitations on warranties. See complete copy of the warranty included with the heater.

Commercial Large Volume Storage Tanks

Unjacketed and Uninsulated Models

Meet or exceed ASHRAE 90.1b (current standard)

Model Number	Capacity		A		B	Required Manway	C Floor to Return Conn. in.	D Hot Water Outlet Conn. Size in.	E Drain Valve in.	Approx. Shipping Weight @125 PSI lbs.
	Actual U.S. Gal.	Nominal U.S. Gal.	Vert. Height in.	Horiz. Length in.	Diameter in.					
N†175N*5A	175	193	67	63	30	—	17½	2½	1	303
N†210N*5A	210	229	79	75	30	—	17½	2½	1	347
N†240N*5A	240	260	89	85	30	—	17½	2½	1	383
N†280N*5A	280	303	103	99	30	—	17½	2½	1	433
N†285N*5A	285	318	76	45	36	—	19	2½	1	550
N†310N*5A	310	344	82	78	36	—	19	2½	1	527
N†320N*5A	320	340	115	111	30	—	17½	2½	1	476
N†340N*5A	340	375	89	85	36	—	19	2½	1	569
N†360N*5A	360	397	94	90	36	—	19	2½	1	559
N†415N*5A	415	449	106	102	36	—	19	2½	1	671
N†435N*5A	435	486	85	81	42	YES	20½	3	1	695
N†453N*5A	453	504	88	51	42	YES	20½	3	1	805
N†465N*5A	465	502	118	114	36	—	19	3	1	743
N†500N*5A	500	572	77	73	48	YES	22	3	1	928
N†505N*5A	505	558	97	51	42	YES	20½	3	1	874
N†515N*5A	515	555	130	126	36	—	19	2½	3	815
N†575N*5A	575	630	109	105	42	YES	20½	3	1	863
N†580N*5A	580	658	88	84	48	YES	22	3	1	1045
N†645N*5A	645	702	121	117	42	YES	20½	3	1	947
N†675N*5A	675	752	100	96	48	YES	22	3	1	1173
N†720N*5A	720	774	133	129	42	YES	20½	3	1	1031
N†765N*5A	765	846	112	108	48	YES	22	3	1	1301
N†790N*5A	790	846	143	139	42	YES	20½	3	1	1101
N†840N*5A	840	940	124	120	48	YES	22	3	1	1428
N†1040N*5A	1040	1128	145	141	48	YES	22	3	1	1652
N†1340N*5A	1340	1457	153	147	54	YES	25½	3	1½	2182
N†1820N*5A	1820	1983	168	168	60	YES	27	3	1½	3110
N†2105N*5A	2105	2276	192	186	60	YES	27	3	1½	3516
N†2395N*5A	2395	2570	216	210	60	YES	27	3	1½	3922
N†2700N*5A	2700	2961	174	168	72	YES	30	3	1½	3851
N†3115N*5A	3115	3384	198	192	72	YES	30	3	1½	4338
N†3530N*5A	3530	3807	222	216	72	YES	30	3	1½	4825
N†4050N*5A	4045	4462	192	93	84	YES	33	3	1½	6009
N†4120N*5A	4120	4406	256	250	72	YES	30	3	1½	5516
N†5695N*5A	5695	6141	262	256	84	YES	33	3	1½	7994

†V = Vertical, H=Horizontal.

*G = Glass Lined (Vitraglas®) (5 Year Warranty).

*D = Double Glass Lined (Vitraglas®) (10 Year Warranty).

*E = Epoxy Lined (1 Year Warranty - Field Repairable).

*S = Stainless Steel Tank (1 Year Warranty).

Example: NV210NG5A.


Tank Options:

- Hand hole (4"x6")
- Manway (12"x16")
- Extra Tappings (1" - 4")
- Flanged Connections (3" - 10")
- 150 psi working pressure (add suffix -5)
- Hydrojet HC® (add suffix -1)

General

Front water connections 3" (76mm) NPT (except where noted). T&P tapping 1¼" (32 mm) NPT. Aquastat tapping ¾" (19mm) NPT. Most storage tanks are manufactured with convex heads and bases. Some manufacturers list the tank capacity as "Nominal". Generally, this is the theoretical capacity calculated assuming a tank was actually manufactured using a flat (instead of convex) head and base. Bradford White lists both Actual and Nominal capacity for comparison purposes.

Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.



For U.S. and Canada field service, contact your professional installer or local Bradford White sales representative.

Sales 800-523-2931 • Fax 215-641-1670 / Technical Support 800-334-3393 • Fax 269-795-1089 • Warranty 800-531-2111 • Fax 269-795-1089

International: Telephone 215-641-9400 • Telefax 215-641-9750 / www.bradfordwhite.com

BRADFORD WHITE-CANADA INC. Sales / Technical Support 866-690-0961 / 905-238-0100 • Fax 905-238-0105 / www.bradfordwhite.com

Built to be the Best™

©2015, Bradford White Corporation. All rights reserved.