


Submitted Model No.: _ Specific Features:



Available LHP Handle Accent Options with Matching Lift Rod Knobs



Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book for finish options and product availability.

LAVATORY FAUCETS

- C-Spout Series
- Two Handle Widespread Deck Mount
- 3 Hole Sink Applications
- 6" to 16" Centers
- Quick-Snap® Installation

STANDARD SPECIFICATIONS:

- · Solid brass fabricated end valve and spout bodies.
- Widespread 6" (152 mm) to 16" (406 mm) centers.
- 5 1/4" (133 mm) long, 4 3/4" (121 mm) high, rigid spout.
- Quick-Snap® installation.
- LHP Less Handle Program. See handle options below.
- 1/4 turn handle stops.
- Hot and cold stems are interchangeable.
- Control mechanism is the rotating cylinder type with stainless steel plate and 180° rotation, with replaceable non-metallic seats operating in stainless steel lined sockets.
- 3/8" O.D. copper supply tubes.
- Models with suffix "WF" and "LHP" supplied with 1/2"-14 NPSM adapters.
- Models have metal drain with pop-up type fitting with plated flange and stopper.

WARRANTY

- · Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.





COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
 ASME A112.18.2 / CSA B125.2
- Indicates ADA compliance to
- ICC/ANSI A117.1
- IAPMO Listed
- CSA Certified

