

Submitted Model No.:

#### Specific Features: \_ ¥ 5 1/2<sup>''</sup> (140 mm) 4 7/8" (124 mm) (102 mm) 6 9/16" (167 mm) (51 mm) 1 11/16' (43 mm) — 2" (51 mm) 2 3/8" (60 mm) 5" (127 mm) ≻ 1 3/8 (35 mm) 2" (51 mm) Max. Deck Thickness 離離 3/8" (9 mm) Compression Fitting 35" (889 mm) 36" (914 mm) 4" (102 mm) – 6 1/2" (165 mm) 嶜 翻 1 5/8" (41 mm) to 2 3/8" (60 mm) 1 5/8" (41 mm) to 2 3/8" (60 mm) 1 5/8" (41 mm) to 2 3/8" (60 mm) 3 1/2" (89 mm) 2 1/8" (54 mm) Dia. 2 1/8" (54 mm) Dia. 2 1/8" (54 mm) Dia. ) m A 3 3/8" (86 mm) 4 3/8" (111 mm)

#### 4 7/8" (124 mm) 1 3/8" (35 mm) Dia. 4 5/8" (117 mm) (102 mm) 1 1/4" (32 mm) Dia. ← 1 1/4" (32 mm) Dia. 1 1/4" — (32 mm) Dia. ► > -Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.

1 3/8

(35 mm) Dia.

DSP-L-500-DST Rev. A

m

L

1 3/8" (35 mm) Dia.

# LAVATORY **FAUCETS**

- Classic Series
- Diamond<sup>™</sup> Seal Technology
- Single Handle Deck Mount
- 3 Hole Sink Applications
- 4" Centerset

### **STANDARD SPECIFICATIONS:**

- 4" (102 mm) centerset.
- 5" (127 mm) long spout.
- Lever and knob handle. Control mechanism is the diamond embedded ceramic disc cartridge.
- Control handle shall return to neutral position when valve is turned off.
- 3/8" O.D. straight, staggered pex supply tubes -35" (889 mm) and 36" (914 mm) long.
- Models with suffix "MPU" have metal drain with pop-up type fitting with plated flange and stopper.
- Models with suffix "PPU" have plastic pop-up type fitting with plated flange and stopper.
- · Models with no suffix have brass drain w/plastic tailpiece.
- Models have a maximum 1.5 gpm flowrate @ 60 PSI.


## WARRANTY

- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.



#### COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- Indicates ADA compliance to ICC/ANSI A117.1
- IAPMO Listed
- CSA Certified



FAUCET COMPANY

55 E. 111th Street, Indianapolis, Indiana 46280 395 Matheson Blvd. E., Mississauga, ON L4Z 2H2 © 2008 Masco Corporation of Indiana