

Submitted Model No.: ________Specific Features: ______

Finished Deck (Standard) Installation 8" (203 mm) Min * (127 mm) Min.* From Wall 3" (76 mm) Min. From Wall 1 5/8" (41 mm) Dia. 1 5/8" (41 mm) Dia. *16" (406 mm) Maximum Without Using Additional Tubing. 1 1/2" (38 mm) Dia. 1 1/2" (38 mm) to 2 1/2" (63.5 mm) Deck Thickness 5/8" O.D. Copper Tube Inlet Tube -Inlet Tube

ODELTA.

ROMAN TUB/WHIRLPOOL FAUCET ROUGH-IN KIT

- Two Handle Roman Tub Rough-In Kit
- Deck Mount
- Three Hole Installation
- 16" (406 mm) Maximum Widespread (without using additional tubing)

ROUGH-IN KIT STANDARD SPECIFICATIONS:

- · Solid fabricated brass end valves.
- · Three hole installation.
- Widespread 16" (406 mm) maximum centers without using additional tubing.
- 5/8" O.D. copper supply inlet tubes.
- 5/8" O.D. corrugated copper supply outlet tubes.
- Deck mount installation.
- Control mechanism is a rotating cylinder type with stainless steel plate and 180° rotation, with replaceable non-metallic seats operating in stainless steel lined sockets.
- Hot and cold stems are interchangeable.
- Temperature and volume controlled with handles.
- Washerless.
- All operating parts shall be replaceable from the top.

NOTE: Trim kit (T2789) must also be ordered to complete installation.

WARRANTY

- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.





COMPLIES WITH:

• ASME A112.18.1 / CSA B125.1

