


Submitted Model No.: _______Specific Features:

(101.6 mm)
(127 mm)
(127 mm)
(127, 5 mm)
(171.5 mm)
(197 mm)
(197 mm)
(23/4"
(170 mm)
(406.4 mm)
(406.4 mm)
(406.4 mm)
(70 mm)

▲ Designate proper finish suffix







TUB AND SHOWER JETTED SHOWER™ TRIM

- Victorian® Collection
- Tub/Shower

STANDARD SPECIFICATIONS:

- Monitor® 18 Series pressure balanced bath mixing valve with Scald-Guard®.
- Maintains a balanced pressure of hot and cold water even when a valve is turned on or off elsewhere in the system.
- Must also order R18442 Jetted Shower XO™ or R18448 Jetted Shower™ tub/shower rough valve body.
- Back to back installation capability.
- Lever volume control handle; temperature adjustment dial.
- Red and Blue graphics indicate hot/cold temperature adjustment.
- Field adjustable to limit handle rotation into hot water zone.
- Maximum dial rotation adjustable between 90° and 180°
- All parts are replaceable from the front of the valve.
- Adjusts for up to 1" wall thickness.

WARRANTY

- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.






COMPLETE VALVE COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASSE 1016

Indicates ADA compliance to ICC/ANSI A117.1

- CSA Certified
- IAPMO Listed





Indianapolis, Indiana 46280 A Division of Masco Corporation of Indiana © 2006 Masco Corporation of Indiana