

GENERAL

Highest quality sink seamlessly drawn of #18 gauge, type 304 (18-8) nickel bearing stainless steel. Self-rimming.

DESIGN FEATURES

Bowl Depths: 10" (large bowl), 8" (small bowl).

Coved Corners: 1-3/4" radius.

Finish: Exposed surfaces are polished and hand blended to a lustrous Lustertone satin finish with a highlighted inside top radius on the sink bowls.

Underside: Fully protected by heavy duty Sound Guard® undercoating to prevent condensation and deaden sound.

OTHER

Drain opening: 3-1/2".

Faucet Holes: Available with 0, 1, 2, 3 or 4, 1-1/2" diameter faucet holes, 4" center to center.

OPTIONAL ACCESSORIES


Cutting Boards: CB1713 and CBT1713 Rinsing Baskets: LKRB1614 and LKERBSS

These sinks comply with ANSI Standard A112.19.3M.



These sinks are listed by the International Association of Plumbing and Mechanical Officials as meeting the requirements of the Uniform Plumbing Code.

Model ILFGR4822L3





SINK DIMENSIONS (INCHES)*

			Inside Each Bowl						Ribbed	Cutout in Countertop (1¹/2" Radius		Number of 11/2" Dia.	Minimum	Ship.
Model Number	Ove	erall W	L	Left W	D	L F	light W	D	Area	Corr	ners) W	Faucet Holes 4" Centers	Cabinet Size	Wt. Lbs.
ILFGR4822L	48	22	16	19	10	11 ¹ / ₂	16	8	171/2	473/8	213/8	0,1,2,3 or 4	53	35
ILFGR4822R	48	22	11 ¹ /2	16	8	16	19	10	171/2	473/8	213/8	0,1,2,3 or 4	53	35

^{*}Length is left to right. Width is front to back.

Suffix "L" (Left) or "R" (Right) denotes sink bowls are left or right of ribbed area.





ALL DIMENSIONS IN INCHES, TO CONVERT TO MILLIMETERS MULTIPLY BY 25.4.

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice.

This specification describes an Elkay product with design, quality and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked