

The safe & affordable install

Applicable for residential or light commercial installations



Quick Swivel SPECS QSWI3000

A Close Up:



The flush mount hanger is slotted to receive a 3/8 lag bolt 16" or 24" on center. It can be attached parallel or perpendicular to the joist.



The square steel tubing cuts down on vibration while 3 hitch-pins add to the safety and sturdiness of the Quick Swivel with "H" bracket.



Our Quick Swivel is made with 14-gauge steel able to hold 200 lbs. The swivel allows for 360 degree rotation for setting the perfect direction of air flow.



Installation can be accomplished in minutes because all necessary hardware is provided. Attaching a Quick Swivel to your unit is fast & stress-free.

*Powder Coated.

Quick Swivel provides you with a non-swinging, rotating platform that is quick, safe, stable and affordable. The Quick Swivel can easily be installed in residential or commercial applications. Turn the Swivel in any direction you need then lock it in place, it's that quick.


Patent Pending

Quick-Sling 391 West Water Street Taunton, MA 02780


P:1.800.699.0453 F:1.800.699.0423

www.Quick-Sling.com


*As of 1/1/2015 Quick-Sling offers a 2-year warranty on steel & workmanship; Quick-Sling products are coated in accordance with ASTM D3451-06.




Flush Mount
to Ceiling Joists
(Perpendicular)




Flush Mount
to Ceiling Joists
(Parallel)



FULLY RETRACTED



Frame Swivels 360°
and Locks into Position



FULLY EXPANDED

QUICK-SLING

QUICK-SLING SWIVEL FLUSH MOUNT H - BRACKET ASSEMBLY DRAWING

www.quick-sling.com
email: info@quick-sling.com
fax: 1-(800)-699-0423

Quick Sling, LLC
391 W. Water Street
Taunton, MA 02780
1-(800)-699-0453