

KOHLER®

Roughing-In

K-1015-H2, K-1016-H2
BODYSPA
FOOTBATH

Product Information

Applicable product:	
Footbath with drain hole at left	K-1015-H2
Footbath with drain hole at right	K-1016-H2

Fixture*:	
Basin area:	
Bathing well	37" (94 cm) x 36" (91.4 cm)
Top area	38" (96.5 cm) x 37" (94 cm)
To overflow:	
Water depth	8-1/4" (21 cm)
Capacity	43 gal (162.8 L)**
Weight	120 lbs (54.4 kg)
* Approximate measurements for comparison only.	
** 37 gal (140 L) min. required for Bodyspa operation.	

Variable-speed pump:	2 Hp	220-240 V	50/60 Hz	6 A
Heater:	4 kW	220-240 V	50/60 Hz	15 A

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI/ELCB):	
Pump/control	220-240 V, 20 A, 50/60 Hz
Heater	220-240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Stud placement is critical. Follow installation instructions for stud pocket preparation.

Allow 83-1/2" (212.2 cm) to 84" (213.4 cm) from sub-floor to finished ceiling or header for proper enclosure installation.

Enclose top of unit to retain heat and contain water spray.

The BodySpa is not designed for steam applications, and may not perform satisfactorily as a steam unit.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

