

FORTE

Features

- Metal construction
- One-piece, self-contained ceramic disc valve allows both volume and temperature control
- Temperature memory allows faucet to be turned on and off at any temperature setting
- High-temperature limit setting for added safety
- Flexible connections for easy installation
- Remote valve
- Available with or without matching finish sidespray
- 7-3/4" (197 mm) swing spout reach
- Lower flow aerator options are available (refer to the Kohler Price Book)
- 2.2 gpm (8.3 lpm) maximum flow rate


Codes/Standards Applicable

Specified model meets or exceeds the following at date of manufacture:

- ADA
- ICC/ANSI A117.1
- CSA B651
- OBC
- ASME A112.18.1/CSA B125.1
- Energy Policy Act of 2005
- **NSF 61**
- All applicable US Federal and State material regulations

REMOTE VALVE KITCHEN SINK **FAUCET** K-10441 **ALSO K-10443**

CSA B651 OBC ADA



Colors/Finishes

- · CP: Polished Chrome
- Other: Refer to Price Book for additional colors/finishes

Specified Model

| Model | Description | Colors/Finis | Colors/Finishes | |
|---------|--|--------------|-----------------|--|
| K-10441 | Remote valve kitchen sink faucet – with sidespray | □ CP | □ Other | |
| K-10443 | Remote valve kitchen sink faucet – without sidespray | □ CP | □ Other | |

Product Specification

The single-handle remote valve kitchen sink faucet shall be of metal construction. Product shall have a maximum flow rate of 2.2 gallons (8.3 L) per minute with lower flow aerator options available (refer to the Kohler Price Book). Product shall feature temperature memory, allowing the faucet to be turned on and off at any temperature setting. Product shall feature a one-piece, self-contained ceramic disc valve, allowing both volume and temperature control. Product shall feature a high-temperature limit setting for added safety, flexible connections for easy installation, 7-3/4" (197 mm) swing spout reach, remote valve. Product shall be available with or without sidespray. Faucet shall be Kohler Model K-

FORTÉ_®

Installation Notes

Install this product according to the installation guide

