

KOHLER®

Roughing-In

K-1131-H, K-1131-FH PROFLEX® 7242 ACRYLIC BATH WHIRLPOOL WITH HEATER

Product Information

Applicable product:	
Bath whirlpool, drop-in	K-1131-H
Bath whirlpool, tile flange, right-hand pump	K-1131-FH

Recommended accessories:	
Trip lever drain	K-11677

Fixture*:	
Basin area:	
Bathing well	53" (134.6 cm) x 26" (66 cm)
Top area	65" (165.1 cm) x 34" (86.4 cm)
To overflow:	
Water depth	15" (38.1 cm)
Capacity	78 gal (295.3 L)
Weight	75 lbs (34 kg)
Drop-in cut-out	70-1/2" (179.1 cm) x 40-1/2" (102.9 cm)
* Approximate measurements for comparison only.	

Pump:	Hp	V	Hz	A
1-speed	1.25	120	60	7.5

Heater:	kW	V	Hz	A
	1.5	120	60	12.5

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 36 lbs/square foot (175 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

