

Tercet®

5' Bath **K-1161**



Features

- Center drain.
- Integral lumbar support and armrests for comfort.

Material

Acrylic

Installation

Drop-in

Recommended Accessories

K-1491 Bath/Whirlpool Pillow K-11677 Bath Drain K-1601 Bath/Whirlpool Footstop K-7213 27" Cable Bath Drain K-7214 27" Cable Bath Drain K-7259 Clearflo Bath Drain K-37382 45" Rough-in Cable Bath Drain



Codes/Standards

CSA B45.5/IAPMO Z124 UL 1795 Greenguard UL 2818 - Gold

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond





(1600 mm)

35"

(889 mm)

35"

(889 mm)

63"


60" (1524 mm)


21"


Tercet® 5' Bath K-1161

No change in measurements if connected with drain illustrated. (K-11677)

Recommended faucet area







Technical Information

19-1/2"

(533 mm) (495 mm)

All product dimensions are nominal.

Installation: Drop-in Drain location: Center

Basin area, bottom: 52" x 38-3/4" (1321 mm x 984 mm)
Basin area, top: 61" x 46-1/4" (1549 mm x 1175 mm)

(737 mm)

60" (1524 mm)

Weight: 91 lbs (41.3 kg)

Minimum floor load: 38 lbs/ft² (185.5 kg/m²)

Water depth: 15" (381 mm)
Water capacity: 96 gal (363.4 L)

Cutout: Drop-in, 57-1/2" x 27-1/2" (1461 mm x

699 mm)

Minimum flat for door: 0" (0 mm)

Notes

29"

(124 mm)

43-3/4"

1-1/2" Bath Drain

(1111 mm)

½-7/8" _r(73 mm)

13-1/8"

(333 mm)

(737 mm)

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

