

Product Information

Applicable product:				
Bath whirlpool	K-1170-H2			
Required accessories:				
Jet trim kit	K-9698			
Recommended accessories:				
Pop-up drain	K-7161-AF			
Fixture*:				
Basin area:				
Bathing well	42" (106.7 cm) x 27" (68.6 cm)			
Top area	54" (137.2 cm) x 30" (76.2 cm)			
To overflow:				
Water depth	16" (40.6 cm)			
Capacity	81 gal (306.6 L)			
Weight	134 lbs (60.8 kg)			
Drop-in cut-out	64-1/2" (163.8 cm) x 40-1/2" (102.9 cm)			
* Approximate measurements for comparison only.				
Pump:	kW	V	Hz	A
1.5 hp	1.5	240	50/60	11

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Earth-Leakage Circuit-Breaker (ELCB):

Pump/control 220/240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 44 lbs/square foot (212 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

This whirlpool is designed for drop-in installation only. It is not suited for use in a three wall alcove with an overhead shower.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

