

KOHLER® Roughing-In

K-1239, K-1239-L, K-1239-R MARIPOSA® BATH WHIRLPOOL

Product Information

Applicable product:				
Bath whirlpool – drop-in	K-1239			
Bath whirlpool – three-wall alcove, left drain (shown)	K-1239-L			
Bath whirlpool – three-wall alcove, right drain	K-1239-R			
Fixture*:				
Basin area:				
Bathing area, bottom	46" (116.8 cm) x 24" (61 cm)			
Bathing area, top	54" (137.2 cm) x 27" (68.6 cm)			
Weight	105 lbs (47.6 kg)			
To overflow:				
Water depth	14" (35.6 cm)			
Capacity	63 gal (238.5 L)			
* Approximate measurements for comparison only.				
Drop-in cutout:		58" (147.3 cm) x 34" (86.4 cm)		
Pump	Hp	V	Hz	A
1-speed	1.25	120	60	7.5

Required minimum access panel:	20" (50.8 cm) x 15" (38.1 cm)
--------------------------------	-------------------------------

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control	120 V, 15 A, 60 Hz
--------------	--------------------

Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for minimum of 44 lbs/square foot (214 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with the drain overflow before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

The apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

■ Recommended Faucet Area

