

## **Product Information**

Applicable product:					
5' bath whirlpool			ŀ	K-1337	
Recommended accessories:					
Drain			k	(-7166-AF	
Fixture*:					
Basin area:					
Bathing well	42" (106.7 cm) x 28" (71.1 cm)				
Top area	55" (139.7 cm) x 40" (101.6 cm)				
To overflow:					
Water depth	15-1/2" (39.4 cm)				
Capacity	73 gal (276.3 L)				
Weight	110 lbs (49.9 kg)				
* Approximate measurements for comparison only.					
Pump:	Нр	V	Hz	A	
1-speed	1.25	120	60	7.5	
Included components:					
Cutout template				1017044-7	

## **Required Electrical Service**

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):				
Pump/control	120 V, 15 A, 60 Hz			
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.				

## **Installation Notes**

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 42 lbs/square foot (207 kg/square meter) loading.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. Pump/Control Access 20" (50.8 cm) W x 15" (38.1 cm) H 11" (27.9 cm) 3-5/8" 21-1/8" (9.2 cm) (53.7 cm) 42-1/4" (107.3 cm) 1-1/4" 60" (152.4 cm) 3-1/4" (8.3 cm) (3.2 cm) 21" (53.3 cm) 2-7/8" (7.3 cm) <sup>[</sup>1" (2.5 cm) 3" (7.6 cm) 1-1/2" OD

