

1.5

1.5

Variable

speed

Product Information

Applicable product:								
Bath whirlpool, pump on left						K-1368-H2		
Bath whirlpool, pump on right						K-1369-H2		
Required accessories:								
Jet trim kit						K-9696		
Recommended accessories:								
Pop-up drain						K-7161-AF		
Fixture*:								
Basin area:								
Bathing well		48" (121.9 cm) x 29" (73.7 cm)						
Top area			66" (167.6 cm) x 36" (91.4 cm)					
To overflow:								
Water de	18" (45.7 cm)							
Capacity		118 gal (446.7 L)						
Weight		170 lbs (77.1 kg)						
* Approximate measurements for comparison only.								
Pump:	Нр		kW	V	Hz		А	

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Earth-Leakage Circuit-Breaker (ELCB): 220/240 V, 20 A, 50/60 Hz Pump/control

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 56 lbs (274 kg).

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

240

50/60

11





