

TRITON_®

Features

- Brass construction
- Brass valve bodies
- · Quarter-turn washerless ceramic disc valves
- For 8" (20.3 cm) centers
- Escutcheon plate
- 2.2 gallons (8.3 L) per minute maximum flow rate
- Lower flow aerator options are available (refer to the Kohler Price Book)
- · Variety of handle style options
- · Available with or without black handspray
- 8-1/8" (20.6 cm) swing spout


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- Energy Policy Act of 1992
- NSF 61
- ADA

KITCHEN SINK BASE FAUCET K-7827-K ALSO K-7825-K

ADA



Colors/Finishes

· CP: Polished Chrome

Accessories

CP: Polished ChromeNA: None applicable

Specified Model

Model	Description	Colors/Finishes
K-7825-K	Kitchen sink faucet without handspray	□ CP
K-7827-K	Kitchen sink faucet with handspray	□CP

Required Ac	ccessories (Includes Two Handles)		ADA	ADA	ADA
K-16010-2	Standard handles OR	□ CP			
K-16010-3	Cross handles OR		□ CP		
K-16010-4	Lever handles OR			□ CP	
K-16010-5	Wristblade lever handles				□ CP

Product Specification

Two-handle kitchen sink base faucet shall be of brass construction. Faucet shall feature brass valve bodies. Faucet shall feature quarter-turn washerless ceramic disc valves, assuring positive handle stop positioning. Faucet shall be rated at 2.2 gallons (8.3 L) per minute. Product shall have lower flow aerator options. Product shall include 8" (20.3 cm) centers, a 8-1/8" (20.6 cm) swing spout, and escutcheon plate. Faucet is available with or without black handspray. Base faucet shall be Kohler Model K-______-K-CP and handles shall be Kohler Model K-16010-______-CP.

TRITON_®

Optional Ac	ccessories	
1011402	Sidespray deep roughing-in kit	□ NA

Installation Notes

Install this product according to the installation guide.

