

Product Information

| | |
|--|-----------------------------------|
| Applicable product: | |
| Two-piece toilet | K-3588 |
| Fixture*: | |
| Configuration | two-piece |
| Water per flush | 1.6 gpf (6 lpf) or .8 gpf (3 lpf) |
| Water depth from rim | 9-3/4" (24.8 cm) |
| Seat post hole centers | 6-1/4" (15.9 cm) |
| Minimum static pressure required | 20 psi (137 kPa) |
| Maximum static pressure | 80 psi (551 kPa) |
| *Approximate measurements for comparison only. | |
| Included components: | |
| Toilet seat | E70004 |
| Waste connector assembly | 1070830 |
| Installation kit | 1052927 |
| Installation template | 1059382 |
| Bowl | K-4308 |
| Tank | K-4472 |

Installation Notes

A 4" D. waste outlet is required for this installation.

A 1" (2.5 cm) gap between the toilet and the wall is required.

A flange is not required for installation of this product. If this installation will be to new construction, do not install a flange on the waste outlet.

This toilet must be secured to the floor using the supplied floor anchors and bolts. If the subfloor is made of thin oriented strand board (OSB), we recommend that 1/2" (1.3 cm) plywood be attached to the subfloor at the floor anchor locations.

Install this product according to the installation guide.

