

Product Information

Applicable product:	
Classic design - left-hand trip lever (shown)	K-3816
Classic design - right-hand trip lever	K-3816-RA
Classic design - Insuliner® tank and left-hand trip lever	K-3816-U
Stately design - left-hand trip lever (shown)	K-3817
Stately design - right-hand trip lever	K-3817-RA
Stately design - Insuliner tank and left-hand trip lever	K-3817-U

Fixture:	
Configuration	two-piece, elongated
Water per flush	1.28 gpf (4.8 lpf)
Passageway	2-1/8" (54 mm)
Water area	11-3/4" (298 mm) x 9-1/2" (241 mm)
Water depth from rim	6-1/8" (156 mm)
Seat post hole centers	5-1/2" (140 mm)

Included components:

Bowl	K-4380
Tank with Classic design OR	K-4433
Tank with Stately design	K-4434
Tank cover with Classic design OR	1052861
Tank cover with Stately design	1052862
Trip lever	K-9167
Bolt cap accessory pack	1013092

Installation Notes

Install this product according to the installation guide.

For back-to-back toilet installations: Use only a 45° double wye fitting.

Will comply with the Americans with Disabilities Act (**ADA**) when installed per the requirements of the 2010 ADA Standards for Accessible Design, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.8 and 3.8.3.9.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

