

K-6536 ASSURE™ BARRIER-FREE KITCHEN SINK

Product Information

Applicable product:	
4-hole sink	K-6536-4
3-hole sink	K-6536-3
Fixture is ADA compliant.	ADA

Fixture*:		
Small basin area	7" (17.8 cm) x 19" (48.3 cm)	
Water depth	3-3/4" (9.5 cm)	
Large basin area	21" (53.3 cm) x 16" (40.6 cm)	
Water depth	5-3/4" (14.6 cm)	
Drain holes	3-5/8" (9.2 cm) D.	
Faucet holes	1-3/8" (3.5 cm) D.	
* Approximate measurements for comparison only.		

Recommended accessories:	
P-Trap	K-9000

Optional accessories:	
Polyethylene cutting board	K-6537
Polypropylene colander	K-6538
Polypropylene drainboard/coated wire dish rack	K-6539
Removable barrier-free shroud	K-6543-A
Duostrainer sink strainer	K-8801

Installation Notes

Install this product according to the installation guide.

Provide clear floor space per ICC/ANSI A117.1 as shown. These also comply with ADA requirements.

Complies with ADA requirement when rim is no higher than 34" (86.4 cm) from finished floor.

Selected garbage disposal MUST NOT interfere with clear floor space.

Fixture dimensions are nominal and conform to tolerances in ASME Standard A112.19.1M.

K-6536-3 10-7/8" 4" (10.2 cm) (27.6 cm) Finished 2-7/8" Wall (7.3 cm)10" (15.2 cm) (25.4 cm) 25-1/2" (64.8 cm) 5-11/16" (14.4 cm) 16-3/4" (42.5 cm) 36" (91.4 cm) 4-7/8" 1/2" (12.4 cm) (1.3 cm) 10-1/4" 6-7/8" 12-1/4" (26 cm) (17.5 cm) (31.1 cm) 34" 1-1/2" OD (86.4 cm) Finished Floor Standard Installation

10-7/8" 4" (10.2 cm) (27.6 cm) 2-7/8" (7.3 cm)

K-6536-4



