

KOHLER® Roughing-In

K-T948, K-T949, K-T950, K-952 STILLNESS® BATH AND SHOWER FAUCET TRIM

Product Information

Applicable faucet trim only:	
Bath and shower trim, blade handle	K-T948-4
Shower only trim, blade handle	K-T949-4
Valve only trim, blade handle	K-T950-4
Bath spout	K-952
* Rite-Temp® valve must be ordered to complete faucet	
Lever handle is ADA compliant	ADA

Applicable Rite-Temp valve only**:	
Rite-Temp® valve without stops OR	K-304-K
Rite-Temp® valve with stops OR	K-304-KS
Rite-Temp® valve with CPVC female stops OR	K-304-KP
Rite-Temp® valve without stops OR	K-305-K
Rite-Temp® valve with stops OR	K-305-KS
HiFlow Rite-Temp® valve with integral stops	K-305-KP
** Required	

Recommended accessories:	
HiFlow Rite-Temp® thin wall installation kit	88526
Optional accessories:	
Deep rough-in kit for Rite-Temp® valve (lever or cross handles)	1016154

Installation Notes



WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

