

Product Information

Applicable product*:		
Bath and shower valve trim – with 1/2" IPS threaded diverter spout	K-T11552-4	
Bath and shower valve trim – with slip-fit diverter spout	K-T11552-4S	
Shower valve trim – less spout	K-T11553-4	
Lever handle complies with the actuation force Accessibility Guidelines of the Americans with Disabilities Act.		ADA
Required accessories*:		
Rite-Temp valve without stops – NPT connections	K-304-K	shown
Rite-Temp valve with stops – CPVC connections	K-304-KP	not shown
Rite-Temp valve with stops – NPT connections	K-304-KS	not shown
HiFlow Rite-Temp valve with stops – NPT connections	K-306-KS	not shown
*A Rite-Temp valve is required.		

Installation Notes

Install the valve trim according to the installation guide.



WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install the Rite-Temp valve according to the installation guide. Avoid cross-flow conditions. Do not install a shut-off device on either valve outlet.

Cap the shower outlet if the deck-mounted spout, diverter, or handshower is connected to the spout outlet.

Install a 7" (17.8 cm) to 18" (45.7 cm) straight pipe or straight tube with single bath elbow between the valve and the wall-mount spout.

