

#### Product Information

Applicable faucet trim only:	
Bath and shower six-prong handle*	K-T130-3D
Bath and shower lever handle*	K-T130-4D
Bath and shower oval handle*	K-T130-9B
Shower six-prong handle*	K-T132-3D
Shower lever handle*	K-T132-4D
Shower oval handle*	K-T132-9B
Valve six-prong handle*	K-T134-3D
Valve lever handle*	K-T134-4D
Lever handle is ADA compliant. <b>ADA</b>	
* Rite-Temp® valve must be ordered to complete faucet.	

Applicable Rite-Temp® valve only (Required):

Rite-Temp® valve without stops <b>OR</b>	K-304-K
Rite-Temp® valve with stops <b>OR</b>	K-304-KS
HiFlow Rite-Temp® valve with integral stops	K-306-KS

#### Installation Notes

**NOTICE:** When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

