

KOHLER® Roughing-In

K-T16115, K-T16116, K-T16139 REVIVAL® BATH AND SHOWER FAUCET TRIM

Product Information

Applicable bath and shower trim only:	
Scroll handle*	K-T16115-4
Traditional handle*	K-T16115-4A
Applicable shower trim only:	
Scroll handle*	K-T16116-4
Traditional handle	K-T16116-4A
Applicable valve trim only:	
Scroll handle*	K-T16139-4
Traditional handle*	K-T16139-4A
*Rite-Temp® valve must be ordered to complete faucet.	
Lever handle is ADA compliant.	ADA

Applicable Rite-Temp® valve only**:	
Rite-Temp® valve without stops OR	K-305-K
Rite-Temp® valve with stops	K-305-KS
** Required	

Recommended accessories:	
HiFlow Rite Temp® thin wall installation kit	88526
Optional accessories:	
Deep roughing-in kit for Rite-Temp® valve (all handles)	73418

Installation Notes



WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

