

Ordering Information

Applicable shower trim only:		
Lever handles with biscuit accents*	K-T313-4F	
Lever handles with polished finish accents*	K-T313-4M	
Lever handles with white accents*	K-T313-4P	
Applicable valve trim only:		
Lever handles with biscuit accents*	K-T309-4F	
Lever handles with polished finish accents*	K-T309-4M	
Lever handles with white accents*	K-T309-4P	
*Rite-Temp valve must be ordered to complete faucet.		
Applicable Rite-Temp valve:		
Rite-Temp valve without stops	K-304-K	not shown**
Rite-Temp valve with stops	K-304-KS	not shown**
HiFlow Rite-Temp valve with integral stops	K-306-KS	not shown**

HiFlow Rite-Temp thin wall installation kit	88526	not shown
**Required for configuration illustrated.		
ADA Lever handle is ADA compliant		

Product Information



WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Installation Notes

Install this product according to the installation guide. Avoid cross-flow conditions. Do not install shut-off device on either valve outlet. Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet. Install straight pipe or tube drop of 7" (17.8cm) to 18" (45.7cm) with single elbow between valve and wall-mount spout.

