

KOHLER® Roughing-In

K-T461, K-T462, K-T463 MEMOIRS® STATELY BATH AND SHOWER FAUCET TRIM

Product Information

Applicable product:	
Bath/shower trim, cross handle	K-T461-3S
Bath/shower trim, faceted lever handle	K-T461-4S
Bath/shower trim, deco lever handle	K-T461-4V
Shower trim only, cross handle	K-T462-3S
Shower trim only, faceted lever handle	K-T462-4S
Shower trim only, deco lever handle	K-T462-4V
Valve trim only, cross handle	K-T463-3S
Valve trim only, faceted lever handle	K-T463-4S
Valve trim only, deco lever handle	K-T463-4V
Rite-Temp® valve must be ordered to complete faucet.	

Lever handles are ADA compliant. **ADA**

Required accessories:	
Rite-Temp® valve without stops OR	K-304-K
Rite-Temp® valve with stops OR	K-304-KS
HiFlow Rite-Temp® valve with integral stops OR	K-306-KS
Rite-Temp® valve with PVC connections	K-304-KP

Recommended accessories:	
HiFlow Rite-Temp® thin wall installation kit	88526
Optional accessories:	
Deep roughing-in kit for Rite-Temp® valve (all handles)	73418

Installation Notes



WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Install the Rite-Temp® valve according to the valve installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mounted spout, diverter, or handshower is connected to the spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

