

KOHLER® Roughing-In

K-T6808, K-T6809, K-T6810 IV GEORGES BRASS® BATH AND SHOWER FAUCET TRIM

Product Information

Applicable faucet trim only:	
Bath and shower cross handle*	K-T6808-3D
Bath and shower lever handle*	K-T6808-4D
Shower cross handle*	K-T6809-3D
Shower lever handle*	K-T6809-4D
Valve cross handle*	K-T6810-3D
Valve lever handle*	K-T6810-4D
*Rite-Temp® valve must be ordered to complete faucet.	
Lever and cross handle is ADA compliant. ADA	

Required accessories:	
Ceramic dial faceplate	K-146
Rite-Temp® valve without stops OR	K-304-K
Rite-Temp® valve with stops OR	K-304-KS
HiFlow Rite-Temp® valve with integral stops	K-306-KS

Optional accessories:	
IV Georges Brass accent kit (For K-6808-3D)	K-6791
IV Georges Brass accent kit (For K-6808-4D)	K-6798
Deep roughing-in kit for K-304 valve (lever handles)	58223
Deep roughing-in kit for K-304 valve (cross handles)	58224
Thin wall installation kit for K-306 valve	88526

Installation Notes



WARNING: Risk of damage to the K-306-KS valve assembly. When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

