

# KOHLER® Roughing-In

## K-T6908, K-T6910, K-T6913 TRITON® BATH AND SHOWER FAUCET TRIM

### Product Information

Applicable faucet trim only:	
Bath and shower standard handle*	K-T6908-2A
Bath and shower lever handle*	K-T6908-4A
Shower standard handle*	K-T6910-2A
Shower lever handle*	K-T6910-4A
Valve standard handle*	K-T6913-2
Valve lever handle*	K-T6913-4
*Rite-Temp® valve must be ordered to complete faucet.	
Lever handle is ADA compliant.	<b>ADA</b>

Applicable Rite-Temp® valve**:	
Rite-Temp® valve without stops <b>OR</b>	K-304-K
Rite-Temp® valve with stops <b>OR</b>	K-304-KS
HiFlow Rite-Temp® valve with integral stops	K-306-KS
** Required	

Recommended accessories:	
HiFlow Rite-Temp® thin wall installation kit	88526
Optional accessories:	
Deep roughing-in kit for Rite-Temp® valve (lever handles)	58223
Deep roughing-in kit for Rite-Temp® valve (standard handles)	58229

### Installation Notes



**WARNING: Risk of damage to the K-306-KS valve assembly.** When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

