

# KOHLER® Roughing-In

## K-T8224, K-T8226, K-T8228 TABORET® BATH AND SHOWER FAUCET TRIM

### Product Information

Applicable faucet trim:	
Bath and shower trim with lever handle	K-T8224-4
Bath and shower trim with swirl lever handle	K-T8224-4A
Shower only trim with lever handle	K-T8226-4
Shower only trim with swirl lever handle	K-T8226-4A
Applicable valve trim only:	
With lever handle	K-T8228-4
With swirl lever handle	K-T8228-4A
Rite-Temp® valve must be ordered to complete trim.	
Handles are ADA compliant.	<b>ADA</b>
Required accessories:	
Without stops <b>OR</b>	K-304-K-NA
With stops <b>OR</b>	K-304-KS-NA
HiFlow valve with integral stops	K-306-KS-NA
Valve system required for configuration illustrated.	

Recommended accessories:	
HiFlow Rite Temp® thin wall installation kit	88526
Optional accessories:	
Deep roughing-in kit for Rite-Temp® valve (lever and T-handle)	58226

### Installation Notes



**WARNING: Risk of damage to the K-306-KS valve assembly.** When using the K-306-KS valve in a fiberglass or acrylic installation, use the thin wall installation kit (88526).

Install this product according to the installation guide.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mounted spout, diverter, or handshower is connected to the spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

