



Buy it for looks. Buy it for life.®

Specifications

DESCRIPTION

- Metal construction with various finishes identified by suffix
- Includes four single-function body sprays
- Includes 7" rainshower showerhead, arm and flange
- Includes four function hand shower with 69" hose assembly, drop ell and slide bar
- Includes digital controller for temperature, flow, & spray outlet on/off control

OPERATION

- Digital Thermostatic control
- Digital control dial controls temperature with LED indicators & numeric readout on LCD screen
- Digital control dial controls the flow rate with LED indicators
- Digital on/off button
- Digital pause button
- Digital spray outlet on/off control with graphics on LCD screen
- 4 digital presents for temperature, flow rate, and spray outlet on/off selections
- Temperature range adjustment from 60 degrees F to 120 degrees F (16 degrees C to 49 degrees C). Factory maximum setting is 115 degrees (46 degrees C)

FLOW


- Showerhead and handshower limited to 2.5 gpm (9.5 L/min)
- Bodysprays limited to 1.75 gpm (6.6 L/min) each

STANDARDS

- Third party certified to meet ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including ASSE 1016
- Digital controller third party certified to meet UL1951
- Digital controller and Remote control third party certified to meet FCC part 15

WARRANTY

- Lifetime limited warranty against finish defects to the original consumer purchaser
- 5 year warranty against leaks, drips and operation defects to the original consumer purchaser
- 5 year warranty against finish defects if used in commercial installations
- 1 year warranty against leaks, drips and operation defects if used in commercial installations



ioDIGITAL™ 3/4" Vertical Spa

Models: 295 series, T3420 series

Optional Remote: A340 series
(Sold separately)

Valve: 3384 (Sold separately)

