# MOEN

Buy it for looks. Buy it for life.®

### DESCRIPTION

- Metal construction with various finishes identified by suffix
- Flexible supply lines with 3/8" compression fittings
- Includes metal pop-up waste assembly
- Option 3-hole deck plate (escutcheon) available (sold separately)
  OPERATION
- Lever style handle
- Temperature controlled by 100° arc of handle travel

#### FLOW

• Flow is limited to 1.5 gpm max (5.7L/min) at 60 psi

#### CARTRIDGE

- 1255<sup>™</sup> Duralast<sup>™</sup> cartridge
- Nonmetallic/nonferrous and ceramic material


#### **STANDARDS**

- Third party certified to WaterSense,<sup>®</sup> ASME A112.18.1/CSA B125.1, and all applicable requirements referenced therein including NSF61/9
   Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA 🛃 for lever handle

## WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations






ALIGN™ Single-Handle Lavatory Faucet

# Models: 6191 series

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 1 HOLE, 1-1/4" MIN. DIA.



# **CRITICAL DIMENSIONS**

(DO NOT SCALE)

SPC14105

0.16/2014 : Schasod 02