MOEN

Specifications

Buy it for looks. Buy it for life.®

FAUCET DESCRIPTION

- · Metal construction with various finishes identified by suffix
- Hydrolock[®] quick connect installation
- Pullout spray with 68" braided hose
- Flexible supply lines with 3/8" compression fittings
 High arc spout provides height and reach to fill or clean large pots while pull out wand provides the maneuverability for cleaning or rinsing
- 360° rotating spout provides ability to install handle on either side

OPERATION

- Lever style handle
- Operates in stream or spray mode in the pullout or retracted position
- When filling a vessel outside the sink, the pause feature conveniently stops the water flow as the wand passes over the counter top
 Temperature controlled by 100° arc of handle travel
- FLOW

Flow is limited to 2.2. gpm (8.3 L/min) at 60 psi

CARTRIDGE


• 1255[™] Duralast[™] cartridge for Single-Handle Faucets

STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including NSF 61/9
- Complies with California Proposition 65 and with the Federal Safe Water Drinking Act
- The backflow protection system in the device consists of two independently
 operating check valves, a primary and a secondary which prevent backflow
- ADA for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations



90°™ Single Handle High Arc Pull Out Kitchen Faucet

Model: 7597 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 1 HOLE, 1-1/2" (38mm) MIN. DIA.

