MOEN

Buy it for looks. Buy it for life.®

DESCRIPTION

- Metal Construction with chrome plated finish
- Pressure balancing cycle valve design with an adjustable temperature limit stop
- 1/2" CC connections
- Includes showerhead, arm, flange and diverter tub spout

OPERATION

- Lever style Handle
- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to $\pm \ 3^\circ$

FLOW

- Showerhead is limited to 2.5 gpm (9.5 L/min) Max CARTRIDGE
- 1222 cartridge design
- Nonmetallic/nonferrous and stainless steel materials
- Accommodates back to back installations

STANDARDS

 Third party certified to meet CSA B-125, ASME A112.18.1M, ANSI A117.1, ASSE 1016, and all applicable requirements referenced therein

Specifications




CHATEAU[°] POSI-TEMP[°] Single-Handle Tub/Shower Valve

Model: L2353

Model: L2363 (with 1/4 Turn Stops)

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations



CRITICAL DIMENSIONS

(DO NOT SCALE)