



Buy it for looks. Buy it for life.®

# Specifications

## FAUCET DESCRIPTION

- Metal construction with chrome plated or stainless finish
- 1/2" IPS connections
- Lever style handles
- Handle inserts include hot (red) and cold (blue) color indicators
- Includes Protégé side spray with Hydrolock® quick connect system

## OPERATION

- Hot side counterclockwise to open (clockwise to close)
- Cold side clockwise to open (counterclockwise to close)

## FLOW

- Aerator is limited to 2.2 gpm (8.3 L/min).

## CARTRIDGE

- 1224 cartridge design
- Nonmetallic, nonferrous and stainless steel material


## STANDARDS

- Designed and manufactured to comply with the requirements of: CSA B-125, ASME A112.18.1M, ANSI A117.1 and all applicable requirements referenced therein
- Certified to ANSI/NSF 61/9
- Complies with California Proposition 65 and with the Federal Safe Water Drinking Act

## WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations

ADA 




## Monticello® with Cathedral™ Spout Two Handle Kitchen Faucet with Protégé Side Spray

(less handle inserts on 7000 series,  
handle inserts included on 80000 series)

**Models:** 7786, 7786SL,  
87786, 87786SL

**Discontinued Models:** 7786CP, 7786P,  
7786W, 7786V, R7786CG/A7785CG,  
R7786/A7785, R7786P/A7785P,  
R7786CPR/A7785CPR, R7786PM/A7785PM,  
R7786BP/A7785BP, R7786ST/A7785ST

**Spout installs through deck holes a minimum of  
1-1/4" (32mm) in diameter. Valves install through  
1-1/8" (28mm) min. diameter hole.**



## CRITICAL DIMENSIONS

(DO NOT SCALE)