STERLI A KOHLER, COMPANY

Features

- Compression molded from our exclusive solid Vikrell® material
- Tongue-and-groove 4-piece modular design allows for easy "snap together" installation
- Convenient shelves provide generous storage
- Shaving ledge and foot rest added for comfort •
- Shower base can be ordered separately
- Durable high-gloss finish
- 10-year consumer/3-year commercial limited warranty
- 42-1/4" (107.3 cm) x 35-1/4" (89.5 cm) x 77" (195.6 cm) rough-in dimensions include nailing flange
- 42" (106.7 cm) x 34" (86.4 cm) x 75-3/4" (192.6 cm) complete unit finished dimensions


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASTM E162
- ASTM E662
- CSA B45.5/IAPMO Z124







72110100

72210100

Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Complete Unit Description	Co	Colors/Finishes	
72110100	42" (106.7 cm) shower base and wall surround, tile wall	0 🗆	□ Other	
72210100	42" (106.7 cm) shower base and wall surround, curve wall	0 🗆	Other	
Model	Age-in-Place Component Description	Co	Colors/Finishes	
72210106	Complete unit with Age-in-Place backers, curve wall	0 🗆	Other	
72212106	Back wall with Age-in-Place backers, curve wall	0 🗆	□ Other	
72205106	End wall set with Age-in-Place backers, curve wall	0 🗆	Other	
72110106	Complete unit with Age-in-Place backers, tile wall	0 🗆	□ Other	
72112106	Back wall with Age-in-Place backers, tile wall	0 🗆	□ Other	
72105106	105106 End wall set with Age-in-Place backers, tile wall		Other	

ENSEMBLE

Technical Information

M	odel	Door maximum width	Door maximum height
	2110100 2210100	38-5/8" (98.1 cm)	70-1/2" (179.1 cm)

Installation Notes

Install this product according to the installation guide. Size the drain cutout to fit the drain assembly that will be used.

Double studding is recommended for pivot shower door installations.

Studs should be positioned roughly as shown.

Both tile and curve wall surrounds share the same dimensions.

