Corina





Description : Corina two-piece elongated Front Bowl, extended height, ADA Compliant

Model Number

compliant:
5232-XXX-0075
5398-XXX-5320 Tank with polished chrome metal trim lever on left hand side (14" rough-in)
5398-XXX-5326 Tank with polished chrome metal trim lever on right hand side (14" rough-in)
5398-XXX-5182 Tank with white plastic trim lever on left hand side (14" rough-in) Compatible item

5398-XXX-5285 Tank with white plastic trim lever on right hand side (14" rough-in)
36-XXX-002 Toilet seat elongated (available only in white color)
44-XXX-009 Toilet seat elongated, soft closing

: 1.6 GPF : 8 7/8" x 8 1/8" : 6 3/4" : 14" Water Consumption Water Surface

Water Depth From Rim Rough-In Minimum Water Pressure

Trap Diameter Trap Seal Depth Shipping Weight

20 psi. Fully glazed 2" ball pass with 2" trap diameter 2 3/8" 5232: 53 lbs. 5398: 51 lbs. 5232: 15 1/8" W X 28 6/8" L X 18 7/8" H 5398: 19 7/8" W X 11 3/8" L X 16" H **Shipping Dimensions**

VitrA Guide 312851
Tank fittings, bolt caps
(white 310359 / bone-biscuit 310306) Installation Guide Included components

Material Vitreous china

Colors

Standards

: 003 White 017 Bone, 068 Biscuit (Basic Colors) "XXX" indicates the color


Meets the American Disabilities Act Guidelines and


: ICC/ANSI A117-1 requirements when installed so top of seat is 17" from the finished floor. Recommended seat for ADA requirements: VitrA 36-XXX-002 ASME A 112.19.2, CSA B45, ADA ICC/ANSI A117-1, LADWP/SPS

(City of Los Angeles)


Warranty : 10 year limited warranty

2





14 3/8"



3

• DIMENSIONS SHOWN FOR THE LOCATION OF THE SUPPLY IS SUGGESTED.

• INSTALLATION INSTRUCTIONS SUPPLIED WITH THE TOILET.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME Standard A 112.19.2, CSA Standard B45. These measurements may be subject to change. No responsibility is assumed for the use of superseded or voided pages.

August, 2008