## Atlantis





Atlantis Two-piece toilet (ROUND FRONT bowl) (BOWL ONLY) 1.6 gpf Description

Model Numbers 5050BXXX-0101

 $6853 BXXX-5347 \ Tank$  with white plastic trim lever on left hand side 12 "rough in 6853BXXX-5348 Tank with chrome plated trim lever on left hand side 12"rough in 6853BXXX-5349 Tank with white plastic trim lever on left hand side, styrofoam lined

6853BXXX-5350 Tank with chrome plated trim lever on left hand side, styrofoam

lined 12" rough in

6853BXXX-5351 Tank with white plastic trim lever on right hand side 12" rough in 6853BXXX-5352 Tank with chrome plated trim lever on right hand side 12" rough in

05-XXX-001 Toilet Seat (with metal hinges, round front) 05-XXX-002 Toilet Seat (with plastic hinges, rount front)

Water Consumption : 1.6 GPF / 6.0 LPF : 8 1/4" x 7 1/8" Water Surface : 6 7/8"

Water Depth From Rim Rough in : 12"

: 20 psi Minimum Water Pressure Trap Diameter

Fully glazed 2" ball pass trapway with 2 1/8" trap diameter Trap Seal Depth

**Shipping Weight** : 5050: 44.6 lbs. 6853: 35.2 lbs.

**Shipping Dimensions** : 5050: 15 1/2"W x 26"L x 16"H

6853: 10"W x 18 7/8"L x 16 7/8"H Installation Guide : VitrA Guide # 312851

Material : Vitreous China Colors : 003 White


017 Bone / 068 Biscuit (Basic colors)

"XXX" indicates the color


Standards : ASME A 112.19.2, CSA B45, LADWP/SPS

Warranty : 10 year limited warranty














May, 2010

• DIMENSIONS SHOWN FOR THE LOCATION OF THE SUPPLY IS SUGGESTED.

• INSTALLATION INSTRUCTIONS SUPPLIED WITH THE TOILET.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME Standard A 112.19.2, CSA Standard B45. These measurements may be subject to change. No responsibility is assumed for the use of superseded or voided pages.