

Submitted Model No.: _____
 Specific Features: _____

<p>51308▲ 2.0 GPM</p> <p>29" (737 mm)</p> <p>60" (1524 mm)</p> <p>H2Okinetic™ Spray Massage Spray Trickle</p>	<p>54433▲-PK 2.0 GPM</p> <p>9 5/16" (237 mm)</p> <p>3 29/32" (99 mm)</p> <p>60" (1524 mm)</p> <p>H2Okinetic™ Spray Massage Spray Trickle</p>
<p>55433▲ 2.0 GPM</p> <p>9 5/16" (237 mm)</p> <p>4" (104 mm)</p> <p>60" (1524 mm)</p> <p>H2Okinetic™ Spray Massage Spray Trickle</p>	<p>59433▲-PK 2.0 GPM</p> <p>60" (1524 mm)</p> <p>H2Okinetic™ Spray Massage Spray Trickle</p>

▲Designate proper finish suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.



HANDSHOWER

- H₂Okinetic[®] Technology Handshower
- 29" Wall Bar, Wall mount or Shower Arm Mount
- Certified Dual Check Valves

STANDARD SPECIFICATIONS:

- ABS hand held shower with three settings - not a positive shut-off
- Adjustable shower arm mount for hands-free showering.
- Wall bar with adjustable height handshower mount. 60" (1524mm) metal stretchable hose.
- Maximum water consumption 2.0 gpm & (7.6 L/min) @ 80 psi.
- Actual water consumption 1.7gpm & (6.4 L/min) @ 45 psi.
- For use with automatic compensating valves rated at 1.5 gpm (5.7 L/min) or less.


WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH

- ASME A112.18.1/CSA B125.1
- EPA WaterSense[®]



55 E. 111th Street, Indianapolis, Indiana 46280
 350 South Edgeware Road, St. Thomas, Ontario Canada N5P 4L1
 © 2013 Masco Corporation of Indiana