

## 37810 SERIES MEDIUM SUMP, 12" HEAVY-DUTY TOP

### APPLICATION

For use in medium traffic areas such as parking decks or industrial plants for any type of floor construction where a square top complements construction or floor finish. Also, where a moderate to heavy flow of liquid is anticipated and a bucket is desired to protect the drain line from debris.

### SPECIFICATION

JOSAM 37810 Series coated cast iron Floor Drain, two-piece medium-deep body with double drainage flange, WEJLOC® non-puncturing flashing collar, weepholes, bottom outlet, square top, heavy-duty, loose-set grate and removable sediment bucket.

### Available Options

-AE LEVELEZE® Adjustable Ext.	-70 Less Bucket
-4 Secondary Flashing Clamp (Use with -AE only)	-84 Stainless Steel Mesh Bucket Liner
-7 Ductile Iron Grate	-88 Supplementary Strainer
-14 Hinged Grate	-92 Galvanized Cast Iron Parts
-VP Secured Grate, Vandal-Proof Screws	-ARE Acid-Resisting Epoxy

**OUTLETS:**

-18 Hinged Grate with Latching Device	-66 No-Hub Side Outlet
-19 C.I. Undergrate with Satin Finish Nikaloy Top	-T Threaded Outlet
-20 C.I. Undergrate with Satin Finish Bronze Top	-X Inside Caulk Outlet
-49 3/4" Primer Tap	-Y Hub Outlet with Gasket, 2"-4"
-50 1/2" Primer Tap	-Z No-Hub Outlet

**SLOT WIDTH 3/8"**

**FOR OUTLET TYPE SPECIFY -T, -X, -Y or -Z**

TYPE NO.	PIPE SIZE	LBS.	TYPE NO.	PIPE SIZE	LBS.
37812	2	56	37815	5	56
37813	3	56	37816	6	56
37814	4	56			

● CONFORMS WITH ASTM-C564.  
○ ADD 1/4" WHEN FURNISHED WITH NIKALOY OR BRONZE TOP.

## 37820 SERIES DEEP SUMP, 12" HEAVY-DUTY TOP & BUCKET

### APPLICATION

For use in medium traffic areas such as parking decks or industrial plants for any type of floor construction where a square top complements construction or floor finish. Also, where a moderate to heavy flow of liquid is anticipated and a bucket is desired to protect the drain line from debris. The deep sump assures rapid drainage.

### SPECIFICATION

JOSAM 37820 Series coated cast iron Floor Drain, two-piece deep body with double drainage flange, WEJLOC® non-puncturing flashing collar, weepholes, bottom outlet, square top, heavy-duty, loose-set grate and removable sediment bucket.

### Available Options

-AE LEVELEZE® Adjustable Ext.	-49 3/4" Primer Tap
-4 Secondary Flashing Clamp (Use with -AE only)	-50 1/2" Primer Tap
-7 Ductile Iron Grate	-70 Less Bucket
-14 Hinged Grate	-84 Stainless Steel Mesh Bucket Liner
-VP Secured Grate, Vandal-Proof Screws	-88 Supplementary Strainer
-18 Hinged Grate with Latching Device	-92 Galvanized Cast Iron Parts
-19 C.I. Undergrate with Satin Finish Nikaloy Top	-ARE Acid-Resisting Epoxy
-20 C.I. Undergrate with Satin Finish Bronze Top	

**OUTLETS:**

-66 No-Hub Side Outlet, 2"-6"
-X Inside Caulk Outlet
-Z No-Hub Outlet

**SLOT WIDTH 3/8"**

**FOR OUTLET TYPE SPECIFY -X or -Z**

TYPE NO.	PIPE SIZE	LBS.	TYPE NO.	PIPE SIZE	LBS.
37822	2	56	37825	5	63
37823	3	58	37826	6	65
37824	4	60	37828	8	67

● GRATE FREE AREA 54 SQ. IN.  
○ ADD 1/4" WHEN FURNISHED WITH NIKALOY OR BRONZE TOP.