KOHLER. Roughing-In

K-1681, K1682 SONATA_® 60″ BATH AND SHOWER MODULE

Product Information

Applicable Product:				
Bath and shower module, left outlet			K-1681	not shown
Bath and shower module, right outlet		t	K-1682	shown
Fixture*:	basin area	top area		
Bathing well	46" (116.8 cm) x 23" (58.4 cm)	54″ (137.2 cm) x 27″ (68.6 cm)		
	water depth	capacity		
To overflow	11-7/8″ (30.2 cm)	55 gal (208.2 L)		
Configuration	1-piece			
Drain	3-3/8" D. (8.6 cm)			
Weight	200 lbs (90.7 cm)			
* Approximate measurements for comparison only				

Installation Notes

Install this product according to the installation guide.

Fixture not drilled for supply fittings.

Shimming is required to level the fixture.

Stud opening tolerance [+ 1/4'' (6 mm) - 0'' (0 mm)]. When a fire rated wall is specified, dimensions are to the inside of the wall board. Some shimming between the stud frame and the fixture may be required.

The K-1657/K-1663 or K-1708/K-1647-PC steam generator/control kit are designed for use with this product. Kohler shall not be responsible for problems encountered due to the installation and use of other manufacturer's steam generators.

Fixture conforms to ANSI Standard Z124.2. All dimensions are nominal.



