

Kelston®

Comfort Height® Toilet K-3754

Features

- Vitreous china.
- Comfort Height® Elongated bowl.
- AquaPiston® flushing system.
- Includes left-hand polished chrome trip lever.
- 1.6 gpf (6.0 lpf).
- 2-1/8" (54 mm) fully glazed trapway.
- 12" (305 mm) rough-in.
- Less seat and supply.
- 11" (279 mm) x 8-3/4" (222 mm) water area.
- 30" (762 mm) x 16-3/4" (425 mm) x 30-1/2" (775 mm).
- Floor mount / Floor outlet.

Optional Accessories

K-4650 Elongated Toilet Seat

K-9385 Left-hand Trip Lever

K-1954 Touchless Toilet Flush Kit

K-4008 Elongated Toilet Seat

K-4108 Elongated Cleansing Toilet Seat

K-4636 Elongated Toilet Seat

K-4652 Elongated Toilet Seat

K-4659 Elongated Toilet Seat

K-4684 Elongated Toilet Seat

K-4688 Elongated Toilet Seat

K-4694 Elongated Toilet Seat

K-4709 Elongated Cleansing Toilet Seat

K-4732 Elongated Toilet Seat

K-4733 Elongated Toilet Seat

K-4737 Elongated Cleansing Toilet Seat

K-4748 Elongated Toilet Seat

K-4774 Elongated Toilet Seat

K-4814 Elongated Toilet Seat

K-4888 Elongated Toilet Seat

K-5588 Elongated Toilet Seat

K-7637 Angle Supply with Stop (single)

K-4712-T Elongated Toilet Seat

K-4761-BN Elongated Toilet Seat

K-4761-CP Elongated Toilet Seat

Components

Product includes:

K-4306 Toilet Bowl

K-4474 Toilet Tank

Additional included component/s: Tank cover, Trip lever, Bolt

cap accessory pack, and Tank accessory pack.



ADA CSA B651 OBC

Codes/Standards

ASME A112.19.7/CSA B45.10 DOE - Energy Policy Act 1992 ADA ICC/ANSI A117.1 CSA B651 OBC

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.


Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
415	7	Black Black™





Kelston®

Comfort Height® Toilet K-3754



Technical Information

All product dimensions are nominal.

Toilet type: Two-piece, Floor-mount

Waste Outlet: Floor

Bowl shape: Elongated front Flush type: AquaPiston Trap passageway: 2-1/8" (54 mm)

Water Consumption

Full: 1.6 gpf (6 lpf)

Water surface size: 11" x 8-3/4" (279 mm x 222 mm)

Rim to water surface: 6" (152 mm)

Rough-in: 12" (305 mm)

Seat-mounting holes: 5-1/2" (140 mm)

Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

The model is acceptable for left-hand Accessible compartment installations only.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing Codes require elongated toilets and elongated, open-front toilet seats in public bathrooms.

Accessibility standards require controls to be located on the open side of the toilet.

