



### Material

- Made from Serica™ composite material.
- Durable, non-porous, 0.2" thick compression-molded wall that is easy to clean and resists chipping and cracking.

### Installation

- Trimmable to customize size and installation.



### Codes/Standards

ASTM E162  
ASTM E662  
Greenguard UL 2818 - Gold


### KOHLER® Limited Warranty – Choreograph™ Walls and Accessories

See website for detailed warranty information.

### Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	W07	Veincut in Dune
	W08	Veincut in Biscuit
	W09	Veincut in Sandbar
	W10	Crosscut in Dune
	W11	Crosscut in Biscuit



### Technical Information

All product dimensions are nominal.

Installation: Individual Wall

### Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

Use non-solvent based construction adhesive. For installation over tile, use 100% silicone sealant.

Corner joints (optional) allow for 3/8" (10 mm) adjustment for out-of-plumb conditions or uneven cuts.

If installing accessories, install 2x4 backing for handrails, shelves, and shower hooks and 2x10 backing for the flip down seat.