



**LAVATORY FAUCET**

- Two handle, metal lever, centerset lavatory faucet with pop-up drain assembly.

**STANDARD SPECIFICATIONS:**

- Maximum flow rate 1.5 gpm @ 60 PSI, 5.7 L/min @ 414 kPa.
- Two handle lavatory faucets for exposed mounting on 3 hole sinks with 4" centers.
- 4 1/2" (115 mm) long, 4 5/8" (117 mm) high spout.
- The fully replaceable, washerless valve design rotates from the full-off position to the full-on position in 90°.
- The valve stems on the hot and cold stems are interchangeable.
- 1/2" - 14 NPSM threaded male inlet shanks.
- Models have drain with pop-up type fitting with plated flange and stopper.

**WARRANTY**

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



**COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2



- Indicates compliance to ICC/ANSI A117.1
- EPA WaterSense®
- Verified compliant with 0.25% weighted average Pb content regulations.